FIELD NOTES

T. 4 N., R. 13 W.

Sections 8, 9, 10.

W.B. Sections 14, 15, 16, 17, 21, 22.

(N.B. Sections 8 and 17)

Compared also with notes loaned by Mr. S.H. Douglass of Saugus and differences shown in parenthesis. (Signed "Dan Marsh").

Copied from Notes loaned by Mr. L. Friel

	R.13 W.						
7.4N.	6	5	4	3	2	1	
	7	4 8	3 9	2 10	171	12	T.4N.
	18	4 17	£ 16	1 15	1 14	13	
	19	20	221	122	23	24	
	30	29	28	27	26	25	
	31	32	33	34	35	36	
	R 13 W.						

MORTH between Sections 14 and 15.

Var. 14°25' E.

The corner of old survey having been destroyed by S.P.R.R., set post 4 ins.sq. 1 ft.in earth, 1 ft.above stone mound 4 ft.dia.at base by 2 ft.high at one of the posts in board fence of S.P.R.R. 6 lks. (Douglass copy has 61 lks.) W. for witness post to corner to Sections 10,11,14 and 15. 50.00 Land mountainous except in valley. Soil let. and 2nd rate. Timber and undergrowth of Pine, Oak and Sycamore.

Var. 14°25' E.

NORTH between Sections 10 and 11.

Counting from true corner I ascend.

32.00

Oross canada bears SE. and ascend. Summit of spur brs. E & W. and descend. The old & sec. corner a Cedar post in large mound of rocks on M. 33.00 40.00 slope of spur.

Cross gulch 13 lks. wide course SE and ascend. 42.25

48.00

Cross copper lode brs. NE & SE (Douglass copy SW), considerable work has been done in former years on this lode but now is abandoned. Falling on steep side of short rocky ridge, not a suitable place to build a mound I set post 4 ins.sq. 1 ft. in earth, 1 ft.above stone mound 4; ft.in dia. at base by 2 ft.high 57 lks.N. of top of ridge for witness post to corner to Sections 2, 3, 10 and 11. Land mountainous. Soil 2nd and 3rd rate. 50.00 Timber and undergrowth of Fine and Oak.

WORTH between Sections 21 and 22.

Var. 14*25' E.

The point for corner to Sections 15, 16, 21 and 22, falling on steep side hill, not a suitable place to build mound set post 4 ins. eq. 1 ft. in earth, 1 ft. above stone mound 4; ft.dia. at base by 2 ft. high 52 lks.S. of (Douglass copy "on") top of spur bearing ## & **50.00** SE, witness post to said corner. Land mountainous. Soil 2nd rate. Timber and undergrowth of pine, oak and bunchgrass.

MORTH between Sections 15 and 16.

Var. 14°25' E.

(Descend - Douglass)

Cross gulch 12 lks. wide course NW (and ascend - Douglass). Summit of spur brs. NW & SE. and descend.

20.75 27.00 39.70 The & section corner as established in former survey which I find standing on the N. slope of ridge. A cedar post in stone mound as per description furnished me.

Cross fence brs. E & W. and in Soledad Canada.

64.50 65.06 Cross ditch brs. E & W. Cross fence brs. E & W.

73.95 74.73 79.34

Center of S.P.R.R. track brs. E & W.

Cross wagon road brs. E & W.
To the SW. corner of J.H. Whitney's house, all traces of the corner have been destroyed by the building, I marked the corner and drive an iron bolt ; in. dis. in ground for corner to Sections 9, 10, 15 and 16. Land mountainous. Soil 1st and 2nd rate.

Timber and undergrowth of Oak, Cedar and Cottonwood.

EAST on a RANDON line between Sections 10 and 15.

Var. 14025' E.

Thru City of Ravenna.

36.50 Gross wagon road enter field and leave Ravenna.
0.00 After diligent search being unable to find old & section corner 40.00 I set temporary one.

65.50 Leave fields and cross wagon road brs. SE & NW.

- 70.00 Leave low bottom land and enter table land. Intersect the N & S. line 42 lks. S. of corner, I run **5**0.00
 - S. 89°42' W. on a TRUE line between Sections 10 and 15. Var. 14025' E.
- Set post 4 ins. dia. 1 ft. in earth, 1 ft. above earth mound 4 ft. dia. at base by 2 ft. high and dug pits 24 x 15 x 12 ins. 5 lks. 40.00 N. for t sec. corner.
- The corner to Sections 9, 10, 15 and 16. Land rolling. Soil 1st and 2nd rate. 80.00 Timber and undergrowth of Cottonwood; Geder and Willow. Jan. 22,1880 (Douglass)

WORTH between Sections 9 and 10.

Var. 14°25' E.

From SW corner of Whitney's house I offset W. 50 lks. to avoid wing of house and ascend steep mountain.

I offset back E. 50 lks. the post for a section corner falling on large boulder I set post 4 ins. dia. 1 ft. in earth and 1 ft. above stone mound 4 ft. dia. at base by 2 ft. high 170 lks. N. for witness post to t section corner.

Summit of spur brs. HE & SW. and descend. A large boulder on line (of descent - Douglass notes).

50.00 50.25 57.00 79.50

Cross gulch 14 lks. wide course SW.

Cross gulch 12 lks. wide course SW.

Set post 4 ins. sq. 1 ft. in earth, 1 ft.above stone mound 44 ft.

dia.at base by 2 ft.high for corner to Sections 3, 4, 9 and 10.

Land mountainous. Soil 3rd rate. (Timbersad undergrowth of pine, 80.00 oak and cedar - Douglass notes)

EAST on a RANDOM line between Sections 3 and 10. (Ascend - Douglass notes) Var. 14-25' E.

40.00

Set temp. & sec. corner. Summit of spur brs. NW & SE. 60.00

65.50 Leave spur and descend.

- Intersect the N & B. line 37 lks. N. of the corner to Sections 2, 3, 10 and 11. From which corner I run H. 89"44' W. on a TRUE line between Sections 3 and 10.
- Var. 14025' E. Set post 4 ins.dia. 1 ft. in earth, 1 ft.above stone sound 4 ft. dia. at base by 2 ft. high for t sec. corner. To corner to Sections 3, 4, 9 and 10. Land sountainous. Soil 2nd rate. 40.13

80.26 Timber and undergrowth of Oak and Cedar.

> WORTH between Sections 20 and 21. Var. 14025' E.

Set stone 10 x 12 x 6 ins. 7 ins. in the ground for corner to Sections 16, 17, 20and 21.
Land mountainous. Soil 1st and 2nd rate. \$0.00 Soil let and 2nd rate. Timber and undergrowth of Pine, Oak, Gedar and Cottonwood.

> NORTH between Sections 16 and 17. Var. 14025' E. (Ascend - Douglass notes)

Set post 4 ins. dia. 1 ft. in earth, 1 ft. above stone mound 4 ft. dia. at base by 2 ft. high for 1 section corner. Summit of spur brs. WE & SW. and descend. Summit of spur brs. WW & SE. 40.00

55.50 78.50

The post corner to Sections 5, 9, 16 and 17, falling on steep side hill, not a suitable place to build mound I marked a Cedar tree 6 ins.dia. on top of knoll 100 lks. West for witness to said corner. **50.00** Soil 2nd rate. (Land mountainous - Douglass notes). Timber and undergrowth of Pine, Oak and Cedar.

EAST on a RANDON line between Sections 9 and 16. Var. 14°25' E. (Descend - Douglass notes)

Oross gulch 15 lks. wide course NW. and ascend. Summit of spur brs. NW & SE. 3.50 16.00

- I find old stake marked appropriately as called for in former survey 25.20 on the ground about 30 lks. Sw. but no indication of a mound, so I continue.
- Leave mountain and enter canada. (Brs. $\underline{NE} \triangleq \underline{SE}$ Douglass notes). Oross road bys. HW & SE. 26.00

29.25 38.10

Cross creek 6 lks. wide course NW.
The old t section corner having been destroyed by S.P.R.R. I set 40.00 temporary one on M. side of R.R.

Cross S.P.R.R. track between tank house and depot.

James O'Reilly's store about 3 chs. M.

Cross road brs. ME & SW. and enter field.

47.50 56.00 56.50 74.00

Leave field and cross road NI & SW.

- Intersect the N & S. line 27 lks. S. of corner to 9, 10, 16 and 15. **60.00** From which corner I run
 - 8. 59°45' W. on a TRUE line between Sections 9 and 16. Var. 14025' E.
- 40.00
- Set post 4 ins.dia. 1 ft. in earth, 1 ft. above stone mound 4 ft.dia. at base by 2 ft. high for t section corner.
 The corner to Sections 5, 9, 16 and 17.
 Land mountainous except in valley. Soil 2nd rate.
 Timber and undergrowth of Pine, Oak and Willow. 80.00

Var. 14025' E. MORTH between Sections 5 and 9. (Descend - Douglass notes).

- 3.00 (Leave mountain and enter Douglass notes) Enter valley of Santa Clara at mouth of canada brs. E & W.
- Cross road in dry bed of Santa Clara brs. E & W. 6.00

Gross S.P.R.R. track brs. E & W. 7.25

Antone Buelas claim W. of line.

12.00

22.50 39.50

- His houseabout 25 chs. W.

 Leave canada 2.50 chs. wide and ascend.

 Summit of spur brs. NE & SW. and descend.

 Cross gulch 12 lks. wide course SE.

 Set post 4 ins. dia. 1 ft. in earth, 1 ft. above dia. at base by 2 ft. high for t section corner.

 Cross canada 201 lks. wide course SE. 1 ft. above stone mound 4 ft. 40.00
- 44.50

62.00

Cross same gulch 12 lks. wide course SW. and ascend.

Summit of spur brs. WE & SW. and descend.

Cross gulch 14 lks. wide course W.

Set post 4 ins. sq. 1 ft. in earth, 1 ft. above stone mound 4 ft. dia.

at base by 2 ft. high for corner to Sections 4, 5, 5 and 9.

Land mountainous. Soil 2nd rate. 79.75 \$0.00 Timber and undergrowth of Pine, Cedar, Oak and Bunchgrass.

EAST on a RANDON line between Sections 4 and 9. Var. 14025' E. (Ascend - Douglass notes)

Summit of spur brs. IN & SE. and descend. 18.00

Cross dry gulch 15 lks. wide course SW. and ascend. 31.00

40.00 Set temporary t sec. corner.

61.QO

- Summit of spur brs. ME & SW. and descend. Intersect the H & S. line 52 lks. S. of corner to Sections 3, 4, 9 79.65 From which corner I run and 10.
 - 8. 59°35' W. on a TRUE line between Sections 4 and 9. Var. 14°25' E.
- 39.84 Set post 4 ins. dis. 1 ft. in earth, 1 ft. above stone mound 4 ft. dis. at base by 2 ft. high for t section corner.

The corner to Sections 4, 5, 8 and 9. 79.68

Soil 2nd rate. Land mountainous. Timber and undergrowth of Pine, Oak and Cedar. Jan. 24, 1880 (Douglass notes)

Var. 14025' E. NORTH between Sections 17 and 18.

The point for corner to Sections 7, 5, 17 and 15 falling on edge of wagon road I set iron spike or bolt in. dia. and 5 ins.long at the point and at 54 lks. W. I set a post 4 ins. sq., 1 ft.in earth, 1 ft. above stone mound 4 ft.dia. at base by 2 ft. high for witness post to said corner. From which brs. a

Live Cak 30 ins. dia. H. 296° E. 54 lks.

Live Cak 35 ins. dia. S. 79° W.145 lks.

This corner is on the 8. side of Santa Clara Valley at foot of mt.

Soil 2nd rate. Timber and undergrowth of Cak and Cedar.

(Land mountainous - Douglass notes) **50.00**

(Land mountainous - Douglass notes)

EAST on a RAWDON line between Sections 8 and 17.
Var. 14°25' E.

Along South side of Santa Clara Valley.

Cross read brs. Mr & SW. 23.00

23.50 34.00 Cross mouth of gulch brs. N.

40.00

- Leave valley and ascend.
 Set temporary & section corner.
 Intersect the N & S. line 42 lks. H.of corner to Sections 5,9,16 80.20 and 17. From which corner I run
 - S. 89°42' W. on a TRUE line between Sections 5 and 17.
 Var. 14°25' E.
- Set post 4 ins.dis. 1 ft.in earth, 1 ft.above stone mound 4 ft. dis. at base by 2 ft. high for d section corner. From which bears an Oak 45 ins. dis. N. 87% W. 185 lks, Antone Buelas house brs. NE. about 12 chs.dist. 40.10
- The corner to Sections 7, 5, 17 and 15.
 Land mountainous except in valley. Soil 2nd rate.
 Timber and undergrowth of Fine, Oak and Willow. 80.20 ---- Jan. 27, 1880 (Douglass notes)

Var. 14*25' K. MORTH between Sections 7 and 5.

Set post 4 ins. sq., 1 ft. in earth, 1 ft. above stone mound 4 ft. dia. at base by 2 ft. high for corner to Sections 5, 6, 7 and 8. This corner is on susmit of spur bearing NW 4 SE. **50.00** Land mountainous. Soil 1st and 2nd rate. Timber and undergrowth of Pine, Oak, Cedar and Bunchgrass.

> EAST on a RANDOM line between Sections 5 and 5. Var. 14°25' E.

1.50 Descend steep mountain.

20.25 32.50 Cross gulch 15 lks. wide course SE. and ascend. Summit of spur brs. SE & NV. and descend. Set temporarily t section corner. Cross gulch 22 lks. wide course S. and ascend. Summit of spur brs. SV & NE.

40.00

- 42.30 59.50 79.86 Intersect the N & S. line 43 lks. S. of cor. to Secs.4,5, S and 9. From which corner I run
 - S. 59°42' W. on a TRUE line between Sections 5 and S. Var. 14025' E.
- Set post 4 ins.dia. 1 ft. in earth, 1 ft.above stone ad. 4 ft.dia. 39.93
- at base by 2 ft. high for t sec. cor.
 To cor. to Secs. 5, 6, 7 and 5.
 Land mountainous. Soil 2nd rate. Timber and undergrowth of 79.86 Pine, Oak, Gedar and Bunchgrass. W. H. Horway. 1880.